

Version 01

Page 1 / 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Orange Solvent Spray Article number: 554201 UFI: RNUG-EK62-N10V-9S3U

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Cleaning agent

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Hager & Werken GmbH & Co. KG

Ackerstr. 1

47269 Duisburg / GERMANY Phone +49(0)203-99269-0 Fax +49 (0)203 29 92 83 Homepage www.hagerwerken.de E-mail info@hagerwerken.de

Address enquiries to

Technical information info@hagerwerken.de
Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0) 551-19240 Giftinformationszentrum-Nord

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Aerosol 1: H222 Extremely flammable aerosol. H229 Pressurised container: May burst if

heated.

Eye Irrit. 2: H319 Causes serious eye irritation.

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.



Date printed 30.04.2021, Revision 30.04.2021 Vers

Version 01

Page 2 / 16

2.2 Label elements

The determination of properties hazardous to health does not take the propellant or carrier

material into account.

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms

<u>-</u>

Signal word DANGER

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}$ C / 122 $^{\circ}$ F.

P280 Wear eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice / attention.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling Contains: 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one,

Eucalyptol, 2,4-Dimethylcyclohex-3-ene-1-carbaldehyde, 2-Methylundecanal. EUH208 May

produce an allergic reaction.

Cleaner, 648/2004/CE, contains: >=30% aliphatic hydrocarbons (propellant)

fragrances

2.3 Other hazards

Environmental hazardsDoes not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable



Date printed 30.04.2021, Revision 30.04.2021 Version 01 Page 3 / 16

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
40 - <60	Ethanol
	CAS: 64-17-5, EINECS/ELINCS: 200-578-6, EU-INDEX: 603-002-00-5, Reg-No.: 01-2119457610-43-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319
	SCL [%]: >= 50: Eye Irrit. 2: H319
20 - <30	Butane
	CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
10 - <20	Propane
	CAS: 74-98-6, EINECS/ELINCS: 200-827-9, EU-INDEX: 601-003-00-5, Reg-No.: 01-2119486944-21-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
1 - <5	iso-Butane
	CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
<0,25	2-Methylundecanal
	CAS: 110-41-8, EINECS/ELINCS: 203-765-0, Reg-No.: 01-2119969443-29-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Skin Sens. 1B: H317 - Aquatic Acute 1: H400 - Aquatic Chronic 1: H410, M-Factor (acute): 1
<0,25	2,4-Dimethylcyclohex-3-ene-1-carbaldehyde
	CAS: 68039-49-6, EINECS/ELINCS: 268-264-1, Reg-No.: 01-2119982384-28-XXXX
	GHS/CLP: Skin Sens. 1: H317 - Aquatic Chronic 3: H412 - Skin Irrit. 2: H315
<0,25	Eucalyptol
	CAS: 470-82-6, EINECS/ELINCS: 207-431-5, Reg-No.: 01-2119967772-24-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - Skin Sens. 1B: H317
<0,25	1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one
	CAS: 54464-57-2, EINECS/ELINCS: 259-174-3, Reg-No.: 01-2119489989-04-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Skin Sens. 1B: H317 - Aquatic Chronic 1: H410 - Aquatic Acute 1: H400, M-Factor (acute): 1, M-Factor (chronic): 1
<0,25	3-methyldodecanonitrile
	CAS: 85351-07-1, EINECS/ELINCS: 286-729-7
	GHS/CLP: Aquatic Acute 1: H400 - Aquatic Chronic 1: H410

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion Do not induce vomiting.

In the event of symptoms seek medical treatment.

4.2 Most important symptoms and effects, both acute and delayed

Headache Vertigo

Nausea, vomiting. Irritant effects Allergic reactions



Version 01

Page 4 / 16

4.3 Indication of any immediate medical attention and special treatment needed

treat symptomatically

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry powder.

Foam.

Extinguishing media that must not

be used

Water.

5.2 Special hazards arising from the substance or mixture

risk of formation of toxic pyrolysis products, carbon monoxide (CO), not combusted

hydrocarbons

Bursting aerosols can be forcibly projected from a fire.

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from all sources of ignition.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous

earth).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.

Avoid spilling or spraying in enclosed areas.

Keep away from all sources of ignition - Refrain from smoking. Take precautionary measures against static discharges.

Do not eat, drink, smoke or take drugs at work. Wash hands before breaks and after work.

Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Do not store together with oxidizing agents.

Keep in a cool place, heat causes increase in pressure and risk of bursting.

Protect from heat/overheating and from sun.



Date printed 30.04.2021, Revision 30.04.2021

Version 01

Page 5 / 16

7.3 Specific end use(s)

See product use, SECTION 1.2



Date printed 30.04.2021, Revision 30.04.2021

Version 01

Page 6 / 16

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Ethanol

CAS: 64-17-5, EINECS/ELINCS: 200-578-6, EU-INDEX: 603-002-00-5, Reg-No.: 01-2119457610-43-XXXX

Long-term exposure: 1000 ppm, 1920 mg/m³

Butane

CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX

Long-term exposure: 600 ppm, 1450 mg/m³

Short-term exposure (15-minute): 750 ppm, 1810 mg/m³

iso-Butane

CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX

Long-term exposure: 600 ppm, 1450 mg/m³, (Butane)

Short-term exposure (15-minute): 750 ppm, 1810 mg/m³

DNEL

Substance			
Ethanol, CAS: 64-17-5			
Industrial, inhalative (vapor), Acute - local effects, 1900 mg/m³			
Industrial, dermal, Long-term - systemic effects, 343 mg/kg bw/d			
Industrial, inhalative (vapor), Long-term - systemic effects, 950 mg/m³			
general population, inhalative (vapor), Acute - local effects, 950 mg/m³			
general population, dermal, Long-term - systemic effects, 206 mg/kg bw/d			
general population, inhalative (vapor), Long-term - systemic effects, 114 mg/m³			
general population, oral, Long-term - systemic effects, 87 mg/kg bw/d			
2-Methylundecanal, CAS: 110-41-8			
Industrial, inhalative, Long-term - systemic effects, 25,2 mg/m³			
Industrial, dermal, Long-term - systemic effects, 7 mg/kg bw/d			
Industrial, dermal, Long-term - local effects, 1.67 mg/cm²			
general population, inhalative, Long-term - systemic effects, 3,1 mg/m³			
general population, inhalative, Long-term - systemic effects, 3,5 mg/kg bw/d			
general population, oral, Long-term - systemic effects, 3,5 mg/kg bw/d			
Eucalyptol, CAS: 470-82-6			
Industrial, dermal, Long-term - systemic effects, 2 mg/kg bw/day			
Industrial, inhalative, Long-term - systemic effects, 7,05 mg/m³			
general population, oral, Long-term - systemic effects, 600 mg/kg bw/day			
general population, inhalative, Long-term - systemic effects, 1,74 mg/m³			
general population, dermal, Long-term - systemic effects, 1 mg/kg bw/day			
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one, CAS: 54464-57-2			
Industrial, inhalative, Long-term - systemic effects, 30 mg/m³			
Industrial, dermal, Long-term - systemic effects, 28,7 mg/kg bw/day			
Industrial, dermal, Long-term - local effects, 648 μg/cm ²			
general population, inhalative, Long-term - systemic effects, 9 mg/m³			
general population, dermal, Long-term - systemic effects, 17,2 mg/kg bw/day			
general population, dermal, Long-term - local effects, 380 μg/cm ²			
tono 140 (0)044 646 353 0 340430	wannoe CB		



Version 01

Page 7 / 16

PNEC

general population, oral, Long-term - systemic effects, 3 mg/kg bw/day
Substance
Ethanol, CAS: 64-17-5
soil, 0,63 mg/kg
sewage treatment plants (STP), 580 mg/l
sediment (seawater), 2,9 mg/kg
oral (food), 0,38 g/kg
freshwater, 0,96 mg/l
seawater, 0,79 mg/l
sediment (freshwater), 3,6 mg/kg
2-Methylundecanal, CAS: 110-41-8
seawater, 0,00018 mg/l
sediment (freshwater), 0,072 mg/kg sediment dw
sediment (seawater), 0,0072 mg/kg sediment dw
soil, 0,0143 mg/kg soil dw
oral (food), 313 mg/kg food
freshwater, 0,00018 mg/l
Eucalyptol, CAS: 470-82-6
seawater, 5,7 µg/L
sewage treatment plants (STP), 10 mg/L
sediment (freshwater), 1,425 mg/kg
sediment (seawater), 0,142 mg/kg
soil, 0,25 mg/kg soil dw
oral (food), 40 mg/kg
freshwater, 57 μg/L
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one, CAS: 54464-57-2
oral (food), 26,7 mg/kg food
freshwater, 4,4 μg/L
seawater, 0,44 µg/L
sewage treatment plants (STP), 10 mg/L
sediment (freshwater), 3,73 mg/kg sediment dw
sediment (seawater), 0,75 mg/kg sediment dw
soil, 2,7 mg/kg soil dw



Date printed 30.04.2021, Revision 30.04.2021 Version 01 Page 8 / 16

8.2 **Exposure controls**

Additional advice on system design Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance

requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

Hand protection 0,7 mm Butyl rubber, >480 min (EN 374-1/-2/-3).

The details concerned are recommendations. Please contact the glove supplier for further

information.

Skin protection Solvent-resistant protective clothing (EN 340)

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Do not inhale aerosols.

Respiratory protection In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear

appropriate respiratory protection.

Short term: filter apparatus, filter AX (DIN EN 14387).

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

not determined

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state aerosol Color colourless Odor characteristic **Odour threshold** not determined pH-value not applicable pH-value [1%] not applicable Boiling point [°C] not applicable Flash point [°C] not determined Flammability (solid, gas) [°C] not applicable Lower explosion limit not determined Upper explosion limit not determined

Oxidising properties no Vapour pressure/gas pressure [kPa] 270

Density [g/cm³] not determined Relative density not determined Bulk density [kg/m³] not applicable Solubility in water partially miscible

No information available. Solubility other solvents

Partition coefficient [n-octanol/water] not determined Kinematic viscosity not determined Relative vapour density not determined **Evaporation speed** not applicable Melting point [°C] not determined not determined **Auto-ignition temperature** Decomposition temperature [°C] not applicable

Particle characteristics No information available.



Date printed 30.04.2021, Revision 30.04.2021

Version 01

Page 9 / 16

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Heat causes increase in pressure and risk of bursting.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Date printed 30.04.2021, Revision 30.04.2021 Version 01 Page 10 / 16

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Based on available data, the classification criteria are not met.

Substance

Ethanol, CAS: 64-17-5

LD50, oral, Rat, 10470 mg/kg (OECD 401)

2-Methylundecanal, CAS: 110-41-8

LD50, oral, Rat, > 5000 mg/kg bw

NOAEL, oral, Rat, 200 mg/kg bw/d

NOAEL, oral, Rat, 20000 ppm

2,4-Dimethylcyclohex-3-ene-1-carbaldehyde, CAS: 68039-49-6

LD50, oral, Rat, >2000 mg/kg bw (Lit.)

Acute dermal toxicity

Based on available data, the classification criteria are not met.

Substance

Ethanol, CAS: 64-17-5

LD50, dermal, Rabbit, > 2000 mg/kg (OECD 402)

2-Methylundecanal, CAS: 110-41-8

LD50, dermal, Rabbit, > 10 ml/kg bw

Acute inhalational toxicity

Based on available data, the classification criteria are not met.

Substance

Butane, CAS: 106-97-8

LC50, inhalative, Rat, 658 mg/L (IUCLID)

Propane, CAS: 74-98-6

LC50, inhalative, Rat, > 1443 mg/l (15 min) (Lit.)

Ethanol, CAS: 64-17-5

LC50, inhalative, Rat, 117-125 mg/l/4h (OECD 403)

Serious eye damage/irritation

Irritant

Calculation method [RL (EC) No. 1272/2008 Annex I 1.1.3.7]

Substance

Ethanol, CAS: 64-17-5

Eye, Rabbit, OECD 405, irritant

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Substance

Ethanol, CAS: 64-17-5

dermal, Rabbit, OECD 404, non-irritating

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

May cause an allergic skin reaction.

Substance

Ethanol, CAS: 64-17-5

dermal, Guinea pig, OECD 406, non-sensitizing

Specific target organ toxicity — single exposure

Based on available data, the classification criteria are not met.



Date printed 30.04.2021, Revision 30.04.2021

Version 01

Page 11 / 16

Substance

Ethanol, CAS: 64-17-5

inhalative, Rat (male), NOAL >20 mg/l, OECD 403

NOAEL, oral, Rat (female), 1730 mg/kg/d, OECD 408, 90d

Specific target organ toxicity — repeated exposure

Based on available data, the classification criteria are not met.

•

Substance

Propane, CAS: 74-98-6

NOAEC, inhalative, Rat, 4437 mg/m³

Ethanol, CAS: 64-17-5

NOAEL, oral, Rat, 1730 mg/kg bw/day, negativ

Eucalyptol, CAS: 470-82-6

NOAEL, oral, Rat, 600 mg/kg bw/day, OECD 407

Mutagenicity

Does not contain a relevant substance that meets the classification criteria.

Substance

Ethanol, CAS: 64-17-5

mouse, OECD 476, negativ

OECD 471, negativ

Ames-test, negativ

Reproduction toxicity

Does not contain a relevant substance that meets the classification criteria.

Substance

Ethanol, CAS: 64-17-5

NOAEL, oral, mouse, 13800 mg/kg bw/day, OECD 416, negativ

Carcinogenicity

Does not contain a relevant substance that meets the classification criteria.

Substance

Ethanol, CAS: 64-17-5

NOAEL, oral, Rat, > 3000 mg/kg bw/day, negativ

Aspiration hazard

Based on available data, the classification criteria are not met.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.



Date printed 30.04.2021, Revision 30.04.2021 Version 01 Page 12 / 16

SECTION 12: Ecological information

12.1 Toxicity

Substance
Ethanol, CAS: 64-17-5
LC50, (48h), Daphnia magna, 12340 mg/l
LC50, (96h), Oncorhynchus mykiss, 13000 mg/l (OECD 203)
EC50, (72h), Algae, 275 mg/l (OECD 201)
EC50, (48h), Selenastrum capricornutum, 12900 mg/l (OECD 201)
2-Methylundecanal, CAS: 110-41-8
LC50, (48h), Oncorhynchus mykiss, > 0,46 mg/l
LC50, (24h), Oncorhynchus mykiss, > 0,46 mg/l
LC50, (96h), Oncorhynchus mykiss, 0,35 mg/l
LC50, (72h), Oncorhynchus mykiss, 0,35 mg/l
EC50, (48h), Daphnia magna, 0,21 mg/l
EC50, (72h), Pseudokirchneriella subcapitata, 0,11 mg/l
NOEC, (96h), Oncorhynchus mykiss, 0,11 mg/l
NOEC, (48h), Daphnia magna, 0,053 mg/l
NOEC, (72h), Pseudokirchneriella subcapitata, 0,057 mg/l
2,4-Dimethylcyclohex-3-ene-1-carbaldehyde, CAS: 68039-49-6
LC50, (96h), fish, >3 mg/L (Lit.)
EC50, (72h), Algae, >6 mg/L (Lit.)
EC50, (48h), Crustacea, >1,5 mg/L (Lit.)
Eucalyptol, CAS: 470-82-6
LC50, (96h), fish, 57 mg/L
EC50, (72h), Algae, 74 mg/L
EC50, (48h), Invertebrates, 100 mg/L

12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant

Contain no organic complexing agents, which do not reach a DOC-elimination grade in appendix 49 after 28d of at least 80% (in accordance to no. 406 of the plant "analysis and

measuring procedure").

AOX-advice: No dangerous components.

Biological degradability not determined

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.



Version 01

Page 13 / 16

12.7 Other adverse effects

Ecological data of complete product are not available.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended)

160504* gases in pressure containers (including halons) containing dangerous substances

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Inland navigation (ADN)

Transport by land according to ADR/RID

1950

1950

Marine transport in accordance with

IMDG

1950

Air transport in accordance with IATA 1950



Version 01

Page 14 / 16

14.2 UN proper shipping name

Transport by land according to

ADR/RID

Aerosols

- Classification Code

5F

- Label

- ADR LQ

1 I

- ADR 1.1.3.6 (8.6)

Transport category (tunnel restriction code) 2 (D)

Inland navigation (ADN)

Aerosols

- Classification Code

5F

- Label



Marine transport in accordance with

IMDG

Aerosols

- EMS

F-D, S-U

- Label

- IMDG LQ

Air transport in accordance with IATA Aerosols, flammable

- Label



14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

Inland navigation (ADN)

2

Marine transport in accordance with 2.1

IMDG

Air transport in accordance with IATA 2.1

14.4 Packing group

Transport by land according to

not applicable

ADR/RID

Inland navigation (ADN) not applicable

Marine transport in accordance with

not applicable

IMDG

Air transport in accordance with IATA not applicable



Version 01

Page 15 / 16

14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

TRANSPORT-REGULATIONS ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2021)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions

for people

Observe employment restrictions for young people.

- VOC (2010/75/CE) 85 %

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H412 Harmful to aquatic life with long lasting effects.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

H319 Causes serious eye irritation.

H225 Highly flammable liquid and vapour.



Version 01

Page 16 / 16

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level EC50 = Median effective concentration

ECB = European Chemicals Bureau EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score LC50 = Lethal concentration, 50%

LD50 = Median lethal dose LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure Aerosol 1: H222 Extremely flammable aerosol. (Bridging principle "Aerosols") H229

Pressurised container: May burst if heated. (Bridging principle "Aerosols")

Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method [RL (EC) No. 1272/2008

Annex I 1.1.3.7])

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position none

Copyright: Chemiebüro®