

Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Tru-Fit Gold

- · Article number: according to Catalog
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU20 Health services
- · Environmental release category ERC2 Formulation into mixture
- · Application of the substance / the mixture Dental material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kentzler-Kaschner Dental GmbH

Mühlgraben 36 D-73479 Ellwangen Tel: +49/7961/90730 Fax: +49/7961/52031 E-Mail: info@kkd-topdent.de

· Further information obtainable from:

During normal business hours

Monday-Thursday 08:30 - 12:30 and 13:00 - 16:30 CET

Friday 08:30 - 12:30 and 13:00 - 15:00 CET

· 1.4 Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg, Tel. +49 761 19240

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

(Contd. of page 1)

#### · Hazard pictograms









GHS02

GHS07

HS08 G

### · Signal word Danger

#### · Hazard-determining components of labelling:

butanone

methyl methacrylate

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*Use explosion-proof electrical/ventilating/lighting equipment.* 

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

· Description: Dental material

· Dangerous compone	· Dangerous components:		
CAS: 78-93-3 EINECS: 201-159-0	butanone <b>♦</b> Flam. Liq. 2, H225; <b>♦</b> Eye Irrit. 2, H319; STOT SE 3, H336	50-75%	
CAS: 7440-50-8 EINECS: 231-159-6	copper substance with a Community workplace exposure limit	10-25%	
CAS: 7440-66-6 EINECS: 231-175-3	zinc powder -zinc dust (stabilized) � Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-10%	
CAS: 108-88-3 EINECS: 203-625-9	toluene  Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	0.1-1%	

(Contd. on page 3)



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

(Contd. of page 2)

CAS: 80-62-6 methyl methacrylate

0.1-1%

EINECS: 201-297-1 Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3

· Additional information:

REACH-Registrierungsnummern in ECHA-Datenbank:

REACH-Registrierungsnr (Butanon).: 01-2119485493-29

REACH-Registrierungsnummer (Zink Pulver Stabilisiert): 1-2119467174-37

REACH-Registrierungsnummer (Kupfer): keine Info

REACH-Registrierungsnummer (TOLUEN): 01-2119471310-51-XXXX

REACH-Registrierungsnummer (Methylmethacrylat): 01-2119452498--28

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Do not leave affected persons unattended.

Take affected persons out into the fresh air.

· After inhalation:

Take affected persons into fresh air and keep quiet.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Inform doctor. Do not give milk or fatty oils.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Carbon dioxide (CO2)
- $\cdot$  5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)



Version number 3 Revision: 03.05.2017 *Printing date 03.05.2017* 

(Contd. of page 3)

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Stockages VDS 3103

Store only in the original receptacle.

Store in a cool location.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

<b>78-9</b> 3	3-3 butanone
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV
7440	-50-8 copper
WEL	Short-term value: 2** mg/m³ Long-term value: 0.2* 1** mg/m³ *fume **dusts and mists (as Cu)
108-8	88-3 toluene
WEL	Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk
80-62	2-6 methyl methacrylate
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

(Contd. of page 4)

#### · Ingredients with biological limit values:

#### 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

DGUV 112-190 Breathing apparatus

Filter type A2

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Fluorocarbon rubber (Viton)

Butyl rubber, BR

Recommended material thickness: Butylkautschuk: 0,50 mm +/- 0,10 mm Fluorkautschuk: 0,75 mm +/- 0,10 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

Basis: DGUV 212-007

Permeation (Fluorkautschuk): + Level 6 (> 240 min) Permeation (Butykautschuk): + Level 6 (> 480 min)

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Butyl rubber, BR

· Not suitable are gloves made of the following materials: Chloroprene rubber, CR

(Contd. on page 6)



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

(Contd. of page 5)

· Eye protection:



 ${\it Tightly sealed goggles}$ 

9.1 Information on basic physical and c	hemical properties
General Information Appearance:	
Form:	Fluid
Colour:	Gold coloured
Odour:	Recognisable
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 80 °C
Flash point:	-4 °C (c.c.)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	514 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive of
	vapour mixtures are possible.
Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
Vapour pressure at 20 °C:	105 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	51.0 %
VOC (EC)	51.00 %

(Contd. on page 7)



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Open fire, hot surfaces, high temperatures
- · 10.5 Incompatible materials: oxidants, acids, bases
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
78-93-3 bi	ıtanone		
Oral	LD50	3300 mg/kg (Ratte)	
Dermal	LD50	5000 mg/kg (Kaninchen)	
108-88-3 t	108-88-3 toluene		
Oral	LD50	5000 mg/kg (Ratte)	
Dermal	LD50	12124 mg/kg (Kaninchen)	
Inhalative	Inhalative LC50/4 h 5320 mg/l (Maus)		
80-62-6 m	80-62-6 methyl methacrylate		
Oral	LD50	7872 mg/kg (Ratte)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging fertility or the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

(Contd. on page 8)



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

(Contd. of page 7)

Butanon: 96 h LC50 Fish (400 mg/L Cyprinodon variegatus) Cupper: 96 h LC 50 Fish (0,0103 mg/l Pimephales promelas)

Zink Pulver, stablisiert: LC50 Fisch (0,182 mg/l Oncorhynchus tshawytscha)

Toluen: 96 h LC 50 Fish (5,80 mg/l Oncorhychus mykiss) Methylmethaacrylat: 96 h(79 mg/L Oncorhyncus mykiss)

- 12.2 Persistence and degradability No further relevant information available. 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

18 01 06\* | chemicals consisting of or containing hazardous substances

- · Uncleaned packaging:
- $\cdot \textbf{Recommendation:} \ Disposal \ must \ be \ made \ according \ to \ of ficial \ regulations.$

SECTION 14	: Transport in	formation

· 14.1 UN-Number · ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name	
$\cdot ADR$	1993 FLAMMABLE LIQUID, N.O.S. (ETHYL METHYL
	KETONE $(METHYL$ $ETHYL$ $KETONE)),$
	ENVIRONMENTALLY HAZARDOUS
· IMDG	FLAMMABLE LIQUID, N.O.S. (Butanone, Zinc powder,
	stabilised-Mixture), MARINE POLLUTANT
· IATA	Flammable liquid, n.o.s. (Butanone, Zinc powder,
	stablized-Mixture)

- · 14.3 Transport hazard class(es)
- · ADR, IMDG



· Class 3 Flammable liquids.

(Contd. on page 9)



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

	(Contd. of page
· Label	3
IATA	
· Class · Label	3 Flammable liquids.
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances zinc powder -zinc dust (stabilized) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids. 339 F-E, <u>S-E</u> B
· 14.7 Transport in bulk according to Anno Marpol and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	IL Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHY) METHYL KETONE (METHYL ETHYL KETONE)), 3, II ENVIRONMENTALLY HAZARDOUS

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- O2 Substances and mixtures which in contact with water emit flammable gases
- E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 100~t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48

(Contd. on page 10)



Printing date 03.05.2017 Version number 3 Revision: 03.05.2017

(Contd. of page 9)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### · Department issuing SDS:

LOGAR Günther Hasel e.K.

Baden-Airpark, Airport Boulevard B 210

D-77836 Rheinmünster Tel: +49(0)7229-1868-163 Fax: +49(0)7229-1868-165

#### · Contact: info@logar.de

## · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

 $CAS:\ Chemical\ Abstracts\ Service\ (division\ of\ the\ American\ Chemical\ Society)$ 

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Tru-Fit Silber

· Article number: according to Catalog

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU20 Health services
- · Environmental release category ERC2 Formulation into mixture
- · Application of the substance / the mixture Dental material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kentzler-Kaschner Dental GmbH

Mühlgraben 36 D-73479 Ellwangen Tel: +49/7961/90730 Fax: +49/7961/52031 E-Mail: info@kkd-topdent.de

· Further information obtainable from:

During normal business hours

Monday-Thursday 08:30 - 12:30 and 13:00 - 16:30 CET

Friday 08:30 - 12:30 and 13:00 - 15:00 CET

· 1.4 Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg, Tel. +49 761 19240

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

butanone

methyl methacrylate

(Contd. on page 2)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 1)

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Dental material

· Dangerous compone	· Dangerous components:	
CAS: 78-93-3	butanone	75.0%
EINECS: 201-159-0	🚸 Flam. Liq. 2, H225; 🕠 Eye Irrit. 2, H319; STOT SE 3, H336	
	aluminium powder (pyrophoric)	20.0%
EINECS: 231-072-3	📀 Pyr. Sol. 1, H250; Water-react. 2, H261	
	methyl methacrylate	1.0%
EINECS: 201-297-1	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Do not leave affected persons unattended.

Take affected persons out into the fresh air.

- · After inhalation: Take affected persons into fresh air and keep quiet.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Inform doctor. Do not give milk or fatty oils.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Carbon dioxide (CO2)
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Stockages VDS 3103

Store only in the original receptacle.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.
- · Storage class: Storage group: 3A
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

(Contd. on page 4)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

80-62-6 methyl methacrylate

WEL | Short-term value: 416 mg/m³, 100 ppm | Long-term value: 208 mg/m³, 50 ppm

- Ingredients with biological limit values:

78-93-3 butanone

BMGV | 70 \( \mu\)mol/L | Medium: urine | Sampling time: post shift | Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

DGUV 112-190 Breathing apparatus

Filter type A2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

Butyl rubber, BR

Recommended material thickness: Butylkautschuk: 0,50 mm +/- 0,10 mm Fluorkautschuk: 0,75 mm +/- 0,10 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

Basis: DGUV 212-007

Permeation (Fluorkautschuk) + Level 6 (> 480 min)

Permeation (Butykautschuk): + Level 6 (> 480 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Butyl rubber, BR

· Not suitable are gloves made of the following materials:

PVC gloves

Neoprene gloves

· Eye protection: Goggles recommended during refilling

- GR



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 4)

SECTION 9: Physical and chemical	properties
. 9 1 Information on hasic physical and chen	nical propertie

· General Information

· Appearance:

Form: Fluid

Colour: Silver-coloured
Odour: Recognisable
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 80 °C

• Flash point: -4 °C (c.c.)

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 400 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 1.8 Vol %

 Upper:
 11.5 Vol %

· Vapour pressure at 20 °C: 105 hPa

Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:

· Viscosity:

Dynamic:Not determined.Kinematic:Not determined.

· Solvent content:

 Organic solvents:
 75.0 %

 VOC (EC)
 75.00 %

Solids content: 24.0 %

• 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Not determined.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Open fire, hot surfaces, high temperatures

(Contd. on page 6)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 5)

- · 10.5 Incompatible materials: oxidants, acids, bases
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values relevant for classification:		
	78-93-3 butanone		
Γ	Oral	LD50	3300 mg/kg (Ratte)
	Dermal	LD50	5000 mg/kg (Kaninchen)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	aste catalogue	٦
18 01 06*	hemicals consisting of or containing hazardous substances	

(Contd. on page 7)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	VIIV.002
ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. solution
IMDG	FLAMMABLE LIQUID, N.O.S. (Butanone-Methacryl
IATA	solution) Flammable liquid, n.o.s. (Butanone-Methylmethacryla
2/12/1	solution)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u>
14.7 Transport in bulk according to Anne	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	(D/E)
· IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. SOLUTION, 3,



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 7)

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Created on 18.04.2016

EG-SD-Nr.240

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H250 Catches fire spontaneously if exposed to air.

H261 In contact with water releases flammable gases.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

#### · Department issuing SDS:

LOGAR Günther Hasel e.K.

Baden-Airpark, Airport Boulevard B 210

D-77836 Rheinmünster Tel: +49(0)7229-1868-163

Fax: +49(0)7229-1868-165

· Contact: info@logar.de

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Pyr. Sol. 1: Pyrophoric solids - Category 1

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· \* Data compared to the previous version altered.



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Tru-Fit Verdünner
- · Article number: according to Catalog
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU20 Health services
- · Environmental release category ERC2 Formulation into mixture
- · Application of the substance / the mixture Thinner, Diluent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kentzler-Kaschner Dental GmbH

Mühlgraben 36 D-73479 Ellwangen Tel: +49/7961/90730 Fax: +49/7961/52031

E-Mail: info@kkd-topdent.de

 $\cdot \textit{Further information obtainable from:}$ 

During normal business hours

Monday-Thursday 08:30 - 12:30 and 13:00 - 16:30 CET

Friday 08:30 - 12:30 and 13:00 - 15:00 CET

• 1.4 Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg, Tel. +49 761 19240

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:
- butanone
- $\cdot \textit{Hazard statements}$

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Dental material

· Dangerous	components:
-------------	-------------

CAS: 78-93-3 butanone Flam. Liq. 2, H225; \$\frac{1}{2}\$ Eye Irrit. 2, H319; STOT SE 3, H336 75.0% EINECS: 201-159-0

· Additional information:

No REACH Number availabel

For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Do not leave affected persons unattended.

Take affected persons out into the fresh air.

· After inhalation:

Take affected persons into fresh air and keep quiet.

Supply fresh air; consult doctor in case of complaints.

- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Inform doctor. Do not give milk or fatty oils.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 2)

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Carbon dioxide (CO2)
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Stockages VDS 3103

Store only in the original receptacle.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: Storage group: 3A
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

(Contd. on page 4)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 3)

#### · Ingredients with biological limit values:

#### 78-93-3 butanone

BMGV 70 µmol/L

70 μmovL Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

DGUV 112-190 Breathing apparatus

Filter type A2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)

Butyl rubber, BR

Recommended material thickness: Butylkautschuk: 0,50 mm +/- 0,10 mm Fluorkautschuk: 0,75 mm +/- 0,10 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Basis: DGUV 212-007

Permeation (Fluorkautschuk) + Level 6 (> 480 min)

Permeation (Butykautschuk): + Level 6 (> 480 min)

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Butyl rubber, BR

· Not suitable are gloves made of the following materials:

Neoprene gloves Natural rubber, NR

· Eye protection: Goggles recommended during refilling

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Clear
• Odour: Recognisable

(Contd. on page 5)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

	(Contd. of page
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	-86 °C
Initial boiling point and boiling range	e: 80 °C
· Flash point:	-4 °C (SFCC)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	514 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air
· · · · · · · · · · · · · · · · · · ·	vapour mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	105 hPa
· Density at 20 °C:	0.95 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	400 cPs
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	75.0 %
VOC (EC)	75.00 %
· 9.2 Other information	No further relevant information available.

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Open fire, hot surfaces, high temperatures
- · 10.5 Incompatible materials: oxidants, acids, bases
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 5)

· LD/LC50 values relevant for classification:		
78-93-3	butan	one
Oral	LD50	3300 mg/kg (Ratte)
Dermal	LD50	5000 mg/kg (Kaninchen)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

18 01 06\* | chemicals consisting of or containing hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

#### **SECTION 14: Transport information**

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1993

(Contd. on page 7)



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

	(Contd. of p
14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. solution
IMDG	FLAMMABLE LIQUID, N.O.S. (Butanone-solution)
IATA	Flammable liquid, n.o.s. (Butanone-solution)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL .
Excepted quantities $(EQ)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
<b>T</b>	Maximum net quantity per outer packaging: 500 ml
Transport category	2 (D(E)
Tunnel restriction code	( <i>D/E</i> )
IMDG	17
Limited quantities (LQ)	IL C-1 F2
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. SOLUTION, 3

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 20.02.2017 Version number 2 Revision: 20.02.2017

(Contd. of page 7)

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Created on 18.04.2016

EG-SB-Nr. 239

### · Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### · Department issuing SDS:

LOGAR Günther Hasel e.K.

Baden-Airpark, Airport Boulevard B 210

D-77836 Rheinmünster Tel: +49(0)7229-1868-163 Fax: +49(0)7229-1868-165

· Contact: info@logar.de

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

 $CAS:\ Chemical\ Abstracts\ Service\ (division\ of\ the\ American\ Chemical\ Society)$ 

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

-GB