

according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

silaplast cat f FUTUR, flüssig

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH
Street: Carl-Zeiss-Straße 4
Place: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

E-mail: post@detax.com Internet: www.detax.com

Responsible Department: This number is only obtainable during office hours

(Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

1.4. Emergency telephone +1-800-424-9300 (CHEMTREC worldwide)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Muta. 2; H341 Repr. 1A; H360F STOT RE 1; H372 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

alkylstannonic siloxanes

Signal word: Danger

Pictograms:





Hazard statements

H302+H332 Harmful if swallowed or if inhaled.
H319 Causes serious eye irritation.

H341 Suspected of causing genetic defects.

H360F May damage fertility.

H372 Causes damage to organs () through prolonged or repeated exposure if swallowed.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing



according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 2 of 8

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH208 Contains menthone, isomenthone. May produce an allergic reaction.

Restricted to professional users.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
93925-42-9	alkylstannonic siloxanes			80 - < 100 %
	300-344-4		01-2119560586-30	
	Muta. 2, Repr. 1B, Skin Sens. 1, STOT SE 1, STOT SE 3, Aquatic Chronic 1; H341 H360 H317 H370 H335 H410			
89-80-5	menthone			0.1 - < 5 %
	201-941-1			
	Skin Irrit. 2, Skin Sens. 1B; H315 H317			
491-07-6	isomenthone			0.1 - < 5 %
	207-727-4			
	Skin Irrit. 2, Skin Sens. 1B; H315 H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Let water be drunken in little sips (dilution effect).





according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 3 of 8

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide



according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 4 of 8

adequate ventilation as well as local exhaustion at critical locations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber), FKM (fluoro rubber), CR (polychloroprene, chloroprene rubber)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid:
Colour: colourless
Odour: characteristic

Test method

Melting point/freezing point: not determined

Boiling point or initial boiling point and >200 °C DIN 51356

boiling range:

Flammability: not applicable not applicable Lower explosion limits: not determined

Upper explosion limits: not determined

Flash point: >100 °C DIN 51755 Auto-ignition temperature: >300 °C DIN 51794

Decomposition temperature: >250 °C pH-Value: not determined Water solubility: The study does not need to be conducted

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: <1 hPa

(at 20 °C)

Density (at 20 °C): 1,0 g/cm³ DIN 51757



according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 5 of 8

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidizing.

Other safety characteristics

Evaporation rate: not determined Solid content: not determined

Viscosity / dynamic: <80 mPa·s BROOKFIELD

(at 23 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Harmful if inhaled.

ATEmix calculated

ATE (oral) 510,0 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 11,22 mg/l; ATE (inhalation dust/mist) 1,530 mg/l

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Contains menthone, isomenthone. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (alkylstannonic siloxanes)

May damage fertility.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards



according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 6 of 8

arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land	trans	port	(ADR	KID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.





according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 7 of 8

14.3. Transport hazard class(es):14.4. Packing group:No dangerous good in sense of this transport regulation.No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%
Acute Tox: Acute toxicity
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
Skin Sens: Skin sensitisation
Muta: Gorm cell mutagenicity

Muta: Germ cell mutagenicity
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicit

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard



according to Regulation (EC) No 1907/2006

silaplast cat f FUTUR, flüssig

Revision date: 01.02.2024 Product code: 10174 Page 8 of 8

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Eye Irrit. 2; H319	
Muta. 2; H341	Calculation method
Repr. 1A; H360F	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method
,	

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
11302	Hailillui II Swalloweu.

H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
 H341 Suspected of causing genetic defects.
 H360 May damage fertility or the unborn child.

H360F May damage fertility.
H370 Causes damage to organs.

H372 Causes damage to organs () through prolonged or repeated exposure if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains menthone, isomenthone. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)